

Norm 5 upright 2000×300 mm

P/N: 0101287 | RG-RS/N5 600kg 2000/300



Technical data

Modular dimension:	150 mm
Max. section load	600
Carbon footprint (TM65 Basic Report)	44 kgCO ₂ e
Weight:	4 kg
Width:	300 mm
Depth:	25 mm
Height:	1960 mm

Similar to illustration, technical modifications reserved. Without decoration.

Modular shelving system made of high-quality stainless steel 1.4301 in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.08" (50 × 2 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request:
06.09.2025, 15:59:07

All information / dimensions are approximate, technical changes reserved. © Hupfer