

Norm 5 upright 2000×400 mm

P/N: 0101297 | RG-RS/N5 600kg 2000/400



Technical data

| | |
|---|------------------------|
| Modular dimension: | 150 mm |
| Max. section load | 600 |
| Carbon footprint (TM65 Basic Report) | 46 kgCO ₂ e |
| Weight: | 5 kg |
| Width: | 400 mm |
| Depth: | 25 mm |
| Height: | 1960 mm |

Similar to illustration, technical modifications reserved. Without decoration.

Modular shelving system made of high-quality stainless steel 1.4301 in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.08" (50 × 2 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request:
11.09.2025, 18:23:21

All information / dimensions are approximate, technical changes reserved. © Hupfer