

## General purpose trolley side panel 2 shelves 800×500 mm



*Similar to illustration, technical modifications reserved. Without decoration.*

### Technical data

|   |                        |
|---|------------------------|
| <b>Modular dimension:</b>                   | 150 mm                 |
| <b>Max. section load</b>                    | 600                    |
| <b>Carbon footprint (TM65 Basic Report)</b> | 31 kgCO <sub>2</sub> e |
| <b>Payload:</b>                             | 80                     |
| <b>Weight:</b>                              | 33 kg                  |
| <b>Width:</b>                               | 900 mm                 |
| <b>Depth:</b>                               | 600 mm                 |
| <b>Height:</b>                              | 950 mm                 |

Modular shelving system made of high-quality stainless steel 1.4301 in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.08" (50 × 2 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request:  
08.05.2026, 09:53:04

*All information / dimensions are approximate, technical changes reserved. © Hupfer*