General purpose trolley 3 shelves 1000×600 mm

P/N: 0112082 | SW 10x6/3



Technical data

we make work flow

| Payload: | 120 kg |
|----------|---------|
| Weight: | 25 kg |
| Width: | 1095 mm |
| Depth: | 695 mm |
| Height: | 950 mm |

Similar to illustration, technical modifications reserved. Without decoration.

Serving trolley in standard version with deep-drawn shelves.

Trolley in robust, self-supporting and hygienic design, made of high-quality stainless steel. Ø 1.0" (25 mm) round tube frame with welded,) deep-drawn shelves with 0.4" (10 mm) high profile edge, lined with sound insulation on the underside, hygienically folded by 1.4" (35 mm) and rebated inwards, designed for easy cleaning. Push bars integrated on both sides into tube frame ensure good manoeuvrability. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, Ø 4.9" (125 mm), with pin fastening.

Time and date of the request:All information / dimensions are approximate, technical changes reserved. © Hupfer01.09.2025, 22:02:25

Hupfer · Dieselstrasse 20, 48653 COESFELD · Postfach 1463, 48634 COESFELD · Tel.: +49 2541 805-0 · Fax: +49 2541 805-111 info@hupfer.com