



### Technical data

<b>Modular dimension:</b>	75 mm
<b>Insertion type:</b>	Lengthwise insertion
<b>Payload:</b>	180
<b>Weight:</b>	31 kg
<b>Width:</b>	813 mm
<b>Depth:</b>	619 mm
<b>Height:</b>	1662 mm

*Similar to illustration, technical modifications reserved. Without decoration.*

Gastronorm trolley in high version for storing GN 1/1 containers and associated partition elements.

Trolley with two compartments in robust, self-supporting and hygienic design, made of high-quality 1.0 × 1.0" (25 × 25 mm) stainless steel. 36 pairs of welded U-shaped shelf rails at distances of 3.0" (75 mm), with push-through and tilt protections on both sides as per DIN EN 18867-2. In addition to the vertical square tubes, two 0.8 × 0.4" (20 × 10 mm) rectangular-profile cross braces per partitionment ensure user-friendly handling. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, ø 4.9" (125 mm), with pin fastening.

The Hupfer gastronorm trolley RWG 2 / 36 GN 75-L-U features a rail spacing of 75 mm, which gives it a 50 % greater capacity (when GN containers without lids with a depth of 150 mm are placed in it) in comparison to other products.