Pre-portioning trolley for 24×EN

P/N: 0113065 | VTW 1/24 EN 115-B-U





Technical data

Modular dimension:	115 mm
Insertion type:	Crosswise insertion
Payload:	220 kg
Weight:	25 kg
Width:	659 mm
Depth:	819 mm
Height:	1652 mm

Similar to illustration, technical modifications reserved. Without decoration.

Open transport trolley for pre-proportioning of cold components on EN trays and for storage and provision in EN insert baskets.

Trolley with one compartment, in robust, self-supporting and hygienic design, made of high-quality stainless steel. Welded U-shaped shelf rails with push-through and tilt protections on both sides as per DIN EN 18867-2. In addition to the vertical square tubes, 2 rectangular-profile cross braces ensure user-friendly handling. Four polymer corner bumpers at the bottom serve as bumpers and protect the equipment on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, ø 4.9" (125 mm), with pin fastening.

Time and date of the request:All information / dimensions are approximate, technical changes reserved. © Hupfer17.07.2025, 12:10:40

Hupfer • Dieselstrasse 20, 48653 COESFELD • Postfach 1463, 48634 COESFELD • Tel.: +49 2541 805-0 • Fax: +49 2541 805-111 info@hupfer.de • www.hupfer.com