

Gastronorm trolley for 40×GN 1/1

P/N: 0119012 | RWG 1/40 GN 75-B-L

HUPFER
we make work flow



Technical data

| | |
|---------------------------|---------------------|
| Modular dimension: | 75 mm |
| Insertion type: | Crosswise insertion |
| Payload: | 200 |
| Weight: | 25 kg |
| Width: | 659 mm |
| Depth: | 739 mm |
| Height: | 1818 mm |

Similar to illustration, technical modifications reserved. Without decoration.

The shelving trolley is used for transporting, temporarily storing, preparing, and distributing GN containers.

Trolley with one compartment in robust, self-supporting and hygienic design, made of high-quality 1.0 × 1.0" (25 × 25 mm) stainless steel. 20 pairs of welded L-shaped shelf rails at distances of 3.0" (75 mm), with push-through protections on both sides as per DIN EN 18867-2. In addition to the vertical square tubes, two 0.8 × 0.4" (20 × 10 mm) rectangular-profile cross braces ensure user-friendly handling. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, ø 4.9" (125 mm), with pin fastening.

- Extensive equipment options allow for customised design and individual usage possibilities
- The design of the rails ensures safe insertion and removal of GN containers
- Swivel castors provide smooth driving and precise manoeuvring
- Locking devices guarantee secure driving and positioning
- High-quality workmanship with premium stainless steel enables easy cleaning and perfect hygiene
- Valuable materials ensure sustainability and value retention
- Robust construction guarantees high stability and load capacity

Time and date of the request: 07.05.2026, 22:11:37 *All information / dimensions are approximate, technical changes reserved. © Hupfer*