HUPFER we make work flow

Gastronorm trolley for 40×GN 1/1

P/N: 0119012 | RWG 1/40 GN 75-B-L



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Modular dimension: 75 mm

Insertion type: Crosswise insertion

 Payload:
 200

 Weight:
 25 kg

 Width:
 659 mm

 Depth:
 739 mm

 Height:
 1818 mm

The shelving trolley is used for transporting, temporarily storing, preparing, and distributing GN containers.

Trolley with one compartment in robust, self-supporting and hygienic design, made of high-quality 1.0×1.0 " (25 \times 25 mm) stainless steel. 20 pairs of welded L-shaped shelf rails at distances of 3.0" (75 mm), with push-through protections on both sides as per DIN EN 18867-2. In addition to the vertical square tubes, two 0.8×0.4 " (20 \times 10 mm) rectangular-profile cross braces ensure user-friendly handling. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, \emptyset 4.9" (125 mm), with pin fastening.

- Extensive equipment options allow for customised design and individual usage possibilities
- The design of the rails ensures safe insertion and removal of GN containers
- Swivel castors provide smooth driving and precise manoeuvring
- Locking devices guarantee secure driving and positioning
- High-quality workmanship with premium stainless steel enables easy cleaning and perfect hygiene
- Valuable materials ensure sustainability and value retention
- Robust construction guarantees high stability and load capacity

Time and date of the request: 23.11.2025, 22:10:17

All information / dimensions are approximate, technical changes reserved. © Hupfer