

# Transport shelving unit

P/N: 0121392 | RTW/Z 12-5/900

**HUPFER**  
we make work flow



## Technical data

|                           |         |
|---------------------------|---------|
| <b>Modular dimension:</b> | 150 mm  |
| <b>Payload:</b>           | 200 kg  |
| <b>Weight:</b>            | 17 kg   |
| <b>Width:</b>             | 1275 mm |
| <b>Depth:</b>             | 575 mm  |
| <b>Height:</b>            | 900 mm  |

*Similar to illustration, technical modifications reserved. Without decoration.*

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.12" (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 × 0.8 × 0.06" (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request:  
02.05.2025, 03:51:27

*All information / dimensions are approximate, technical changes reserved. © Hupfer*