Transport shelving unit

P/N: 0121393 | RTW/Z 12-6/900

HUPFER
we make work flow

Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Modular dimension:	150 mm
Payload:	200 kg
Weight:	17.525 kg
Width:	1275 mm
Depth:	675 mm
Height:	900 mm

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 × 1.0'' (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.12'' (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded ø 0. 28'' (7 mm) shelf bolts at distances of 5.9'' (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 × 0.8 × 0.06'' (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, ø 4.9'' (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 12-6/900 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request:
28.04.2024, 04:19:55

All information / dimensions are approximate, technical changes reserved. © Hupfer

Hupfer · Dieselstrasse 20, 48653 COESFELD · Postfach 1463, 48634 COESFELD · Tel.: +49 2541 805-0 · Fax: +49 2541 805-111
info@hupfer.de · www.hupfer.com