



Technical data

| Payload: | 200 kg |
|----------|---------|
| Weight: | 18 kg |
| Width: | 1275 mm |
| Depth: | 575 mm |
| Height: | 1200 mm |

Similar to illustration, technical modifications reserved. Without decoration.

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0×1.0 " (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0×0.12 " (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded ø 0. 28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four $2.0 \times 0.8 \times 0.06$ " (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, ø 4.9" (125 mm), with back-hole fastening.

Time and date of the request:All information / dimensions are approximate, technical changes reserved. © Hupfer25.08.2025, 22:53:31

Hupfer · Dieselstrasse 20, 48653 COESFELD · Postfach 1463, 48634 COESFELD · Tel.: +49 2541 805-0 · Fax: +49 2541 805-111 info@hupfer.de · www.hupfer.com