

## Norm 35 upright 1800×610 mm

P/N: 0126012 | RG-RS/N35 1800/610

**HUPFER**  
we make work flow



### Technical data

|   |                        |
|---|------------------------|
| <b>Modular dimension:</b>                   | 150 mm                 |
| <b>Max. section load</b>                    | 2000                   |
| <b>Carbon footprint (TM65 Basic Report)</b> | 96 kgCO <sub>2</sub> e |
| <b>Weight:</b>                              | 10 kg                  |
| <b>Width:</b>                               | 610 mm                 |
| <b>Depth:</b>                               | 30 mm                  |
| <b>Height:</b>                              | 1800 mm                |

*Similar to illustration, technical modifications reserved. Without decoration.*

Modular shelving system made of high-quality stainless steel in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for stand-alone placement, freely extendable lengthwise.

Uprights made of 1.2 × 1.2" (30 × 30 mm) square tubes, connected by welded upright spokes made of 2.4 × 0.16" (60 × 4.0 mm) flat profiles that also serve as possibility for permanently attaching shelves. Additional attachment options through shelf lugs that are welded to the uprights in a 5.9" (150 mm) grid, enabling two included hook-on elements per upright to be attached variably. Upper covering caps made of plastic and height-adjustable aluminium screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright.

Time and date of the request:  
05.09.2025, 22:32:41

*All information / dimensions are approximate, technical changes reserved. © Hupfer*