

Norm 35 upright 2000×610 mm

P/N: 0126052 | RG-RS/N35 2000/610

HUPFER
we make work flow



Technical data

Modular dimension:	150 mm
Max. section load	2000
Carbon footprint (TM65 Basic Report)	102 kgCO ₂ e
Weight:	10 kg
Width:	610 mm
Depth:	30 mm
Height:	2000 mm

Similar to illustration, technical modifications reserved. Without decoration.

Modular shelving system made of high-quality stainless steel in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for stand-alone placement, freely extendable lengthwise.

Uprights made of 1.2 × 1.2" (30 × 30 mm) square tubes, connected by welded upright spokes made of 2.4 × 0.16" (60 × 4.0 mm) flat profiles that also serve as possibility for permanently attaching shelves. Additional attachment options through shelf lugs that are welded to the uprights in a 5.9" (150 mm) grid, enabling two included hook-on elements per upright to be attached variably. Upper covering caps made of plastic and height-adjustable aluminium screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright.

Time and date of the request:
30.05.2025, 06:42:40

All information / dimensions are approximate, technical changes reserved. © Hupfer