

## Norm 35 upright 2000x610 mm

P/N: 0126052 | RG-RS/N35 2000/610

**HUPFER**  
we make work flow



### Technical data

|  |   |
|--|---|
| <b>Modular dimension:</b>                      | 150 mm                                  |
| <b>Max. section load</b>                       | 2000                                    |
| <b>Carbon footprint (TM65 Midlevel Report)</b> | 95 kgCO <sub>2</sub> e                  |
| <b>TM65 Midlevel Report</b>                    | <a href="#">Link to the certificate</a> |
| <b>Weight:</b>                                 | 10 kg                                   |
| <b>Width:</b>                                  | 610 mm                                  |
| <b>Depth:</b>                                  | 30 mm                                   |
| <b>Height:</b>                                 | 2000 mm                                 |

*Similar to illustration, technical modifications reserved. Without decoration.*

The stainless steel shelving upright with lateral longitudinal connectors serves as a reinforced support component for the Norm 35 freestanding shelving unit. The welded bolts are used to hang the shelf supports at regular height intervals. Two uprights with at least two supports form a shelf. In combination with other components, this shelving upright can bear particularly high loads and is suitable for continuous use in ambient temperatures ranging from -40°C to +60°C.

The stainless steel shelving upright with lateral longitudinal connectors forms a stable single component that provides a reinforced side support for the Hupfer Standregal Norm 35. The welded bolts allow for effortless hanging of the shelf supports at regular height intervals. Two uprights with at least two supports form a shelf. In combination with other components, this shelving upright can bear particularly high loads.

The modular design allows for an assembly-friendly installation of the shelving upright into the stand shelf and a simple, tool-free expansion of the entire shelving unit. Floor unevenness and temperatures from -40°C to +60°C also pose no long-term problem.

- Stable construction with additional lateral longitudinal connectors guarantees high stability and particularly high load capacity
- Modular system allows for installation-friendly assembly and easy, tool-free expansion

Time and date of the request:  
20.02.2026, 19:48:27

All information / dimensions are approximate, technical changes reserved. © Hupfer

**Norm 35 upright 2000x610 mm**

P/N: 0126052 | RG-RS/N35 2000/610

- High-quality workmanship with premium stainless steel enables easy cleaning and perfect hygiene
- Modular system ensures easy handling from assembly to cleaning with minimal effort
- Valuable materials ensure sustainability and preservation of value