

Basket trolley for 5 baskets

P/N: 0128872 | KTW 1/5 50-50

HUPFER
we make work flow



Technical data

Modular dimension:	150 mm
Payload:	80
Weight:	18 kg
Width:	638 mm
Depth:	630 mm
Height:	1062 mm

Similar to illustration, technical modifications reserved. Without decoration.

Basket transport trolley in low version for empty and loaded 19.7 × 19.7" (500 × 500 mm) crockery baskets.

Trolley made entirely of high-quality stainless steel, robust, self-supporting and hygienic design. Tubular frame rack made of square tubes with plastic end caps and welded L-shaped shelf rails for holding 19.7 × 19.7" (500 × 500) to 20.3 × 20.3" (515 × 515 mm) baskets at distances of 5.9" (150 mm). Push-through protections on both sides as per DIN EN 18867-2. Cover plate folded on all sides, rebated inwards, with sound insulation on the underside, as worktop or storage space for additional basket. Gallery on three sides made of round tubes, permanently fixed to the side pillars, also usable as push bar thanks to ergonomic design. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, ø 4.9" (125 mm), with pin fastening.

The Hupfer basket transport trolley KTW 1/5 50-50 has outstanding handling properties due to its very low empty weight in comparison to other products and a gallery that can be used as a push bar, as well as the greatest usable height of 145 mm between the shelf rails.

Illustration shows optional equipment. Version without drip tray.

Time and date of the request: 08.05.2026, 10:27:51 *All information / dimensions are approximate, technical changes reserved. © Hupfer*