

## Norm 25 upright 1800x600 mm

P/N: 0137005 | RG-RS/N25 600kg 1800/600



### Technical data

<b>Modular dimension:</b>	150 mm
<b>Max. section load</b>	600
<b>Carbon footprint (TM65 Midlevel Report)</b>	40 kgCO <sub>2</sub> e
<b>TM65 Midlevel Report</b>	<a href="#">Link to the certificate</a>
<b>Weight:</b>	4 kg
<b>Width:</b>	600 mm
<b>Depth:</b>	25 mm
<b>Height:</b>	1810 mm

*Similar to illustration, technical modifications reserved. Without decoration.*

Modular shelving system made of high-quality stainless steel in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.08" (50 × 2 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves.