

## Norm 25 upright 1800x400 mm

P/N: 0137007 | RG-RS/N25 600kg 1800/400

**HUPFER**  
we make work flow



### Technical data

|  |   |
|--|---|
| <b>Modular dimension:</b>                      | 150 mm                                  |
| <b>Max. section load</b>                       | 600                                     |
| <b>Carbon footprint (TM65 Midlevel Report)</b> | 42 kgCO <sub>2</sub> e                  |
| <b>TM65 Midlevel Report</b>                    | <a href="#">Link to the certificate</a> |
| <b>Weight:</b>                                 | 4 kg                                    |
| <b>Width:</b>                                  | 400 mm                                  |
| <b>Depth:</b>                                  | 25 mm                                   |
| <b>Height:</b>                                 | 1810 mm                                 |

*Similar to illustration, technical modifications reserved. Without decoration.*

Modular shelving system made of high-quality stainless steel in hygienic construction according to DIN 18868-2, suitable for continuous use at temperatures from -40 °C to +60 °C, for installation in a straight line or as corner construction with corner connection brackets, extendable in length as required.

Shelf stand made of square tubes 25 × 25 mm, connected and stabilised by firmly pressed cross-running support rungs 50 × 2 mm. Upper cover caps made of plastic and height-adjustable screw feet to compensate for floor unevenness up to 25 mm as a hygienic finish of the shelf stand. Firmly welded support pins ø 7 mm at a distance of 150 mm for easy hanging of the shelf boards.

Time and date of the request:  
13.02.2026, 00:16:39

*All information / dimensions are approximate, technical changes reserved. © Hupfer*