



Technical data

Payload:	120 kg
Weight:	30 kg
Width:	1095 mm
Depth:	695 mm
Height:	1012 mm

Similar to illustration, technical modifications reserved. Without decoration.

Clearing trolley with deep-drawn shelves.

Trolley in robust, self-supporting and hygienic design, made of high-quality stainless steel. Closed, continuous round tube frame with welded, deep-drawn shelves with profile edge, lined with sound insulation on the underside, hygienically folded and rebated inwards, designed for easy cleaning. As standard, both shelves are equipped with reinforcement struts on the underside, consisting of one diagonal and two longitudinal struts that are fully welded to each other. Upper shelf with welded, 3-sided stainless steel apron. Push bars integrated on both sides into tube frame ensure good manoeuvrability. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks, ø 4.9" (125 mm), fastened to additional reinforcement crossbars by means of screw-on plates and several screws.

The Hupfer clearing trolley ARW $10 \times 6 / 2$ HS is a welded model delivered ready for use, and has a particularly high upstand as a transport guard for the upper shelf in comparison to other products, with castors featuring a particularly sturdy attachment to mounting plates affixed by four bolts each, as well as an extensive range of additional options to choose from.

Time and date of the request:All information / dimensions are approximate, technical changes reserved. © Hupfer26.07.2025, 10:31:52