

## Incounter plate dispenser statically heated **190-260**



Similar to illustration, technical modifications reserved. Without decoration.

## **Technical data**

Payload: 130 kg Capacity: 1000 W **Supply voltage:** 220 V **Nominal current:** 4,2 A **Protection class:** Class I Frequency: 50 Hz Weight: 26 kg Width: 435 mm Depth: 626 mm Height: 823 mm

Plate dispenser for installation into a worktop, for storing Ø 7.5-10. 2" (190-260 mm) round plates in two statically heated stacking compartments.

Dispenser in robust and hygienic design, made of high-quality stainless steel. Closed design for installation from above with shelf frame. Open stacking compartments and two stacking platforms in plastic-coated rod design to prevent crockery discolourations. Stacking compartments with three plastic-coated crockery guides each, variably adjustable without tools. Consistent output heights thanks to manually adjustable stainless steel tension spring systems. Easy cleaning of stacking compartments from above and via a cleaning opening in the base plate. Reduced temperature losses and heating time thanks to cover hoods made of polycarbonate with 3-point locking mechanism. Heating through stainless steel tubular heating element, infinitely variable using thermostat toggle switch on the equipment, with temperature limiter as per VDE. Current supply via a connecting cable set consisting of two connecting cables with earthed plug and equipment plug and an On/Off switch with integrated indicator light as disconnector.

The Hupfer incounter plate dispenser EBR-TE/H 2/19-26 has an adjustable guide that protrudes 57 mm above the support frame and which can be fixed in a base plate, and the use of non-rusting stainless steel springs that are easy to insert and remove provides optimal adjustment options for different crockery diameters and loads. The vertical installation of the heating elements ensures a particularly uniform distribution of heat. The on/off switch can be conveniently integrated into the worktop and requires a cut-out measuring  $30 \times 22$  mm.

Time and date of the request: 20.07.2025, 09:36:50

All information / dimensions are approximate, technical changes reserved. © Hupfer