

## Basket dispenser for plastic components cooling we make work flow slots 570×570 mm



## Similar to illustration, technical modifications reserved. Without decoration.

## **Technical data**

**Capacity:** bis zu 306 Teile (ohne Haube)

760 mm

Payload: 80 kg Weight: 49 kg

Width: 851 mm

Depth: Height: 908 mm

Closed platform dispenser with height-adjustable platform for preparing cold dishes, for storing up to 9 stacks of plastic insulation elements and for cooling in cooling space according to need.

Dispenser in self-supporting and hygienic design, made of high-quality stainless steel. Closed outer housing with cooling slots on all four sides, with a stacking compartment including compartment inner panelling consisting of vertical plastic-coated struts. Removable guide basket made of plastic-coated steel wire as stacking platform with ball bearing platform guide. Consistent output height thanks to manually adjustable stainless steel tension spring system. Easy cleaning of stacking compartment from above and via a cleaning opening in the base plate. Four massive polymer corner bumpers, of which two at the upper corners of the structure that serve as bumpers and protect the equipment on all sides as well as building-side walls from being damaged, with integrated, ergonomically-shaped push bars. Dispenser runs on 4 swivel casters of which 2 with total locks, ø 4.9" (125 mm), fastened by means of screw-on plates and several screws.

The Hupfer platform dispenser BDK 57-57 K has a body with all-round cooling slots to ensure a rapid exchange of air for the wares needing cooling, as well as two push handles installed on the corners of the unit to ensure optimal handling properties. The ergonomically shaped push handles also guarantee effective protection against injuries to the hands. The installation height of 900 mm is the standard working height in food distribution.

Time and date of the request: 09.06.2025, 03:00:53

All information / dimensions are approximate, technical changes reserved. © Hupfer