

Köhler® banquet trolley fan-assisted cooling 40×GN 1/1

HUPFER
we make work flow



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Modular dimension:	57.5 mm
Insertion type:	Crosswise insertion
Payload:	200 kg
Capacity:	260 W
Cooling capacity:	348 W
Supply voltage:	220 V
Nominal current:	1,6 A
Protection class:	Class I
Frequency:	50 Hz
Weight:	159 kg
Width:	795 mm
Depth:	895 mm
Height:	1873 mm

Banquet trolley for holding constituents of meals on GN 2/1 or 1/1 gratings or in GN containers with lid.

Trolley made entirely of high-quality stainless steel, self-supporting design. Double-walled banquet trolley, closed on all sides, wall and doors thermally insulated CFC-free. Double-walled double-wing door with spring-supported door lock made of plastic, can be opened by 270° with one hand. Automatic door blocking when closed or open. Easy cleaning of trolleys. Interior with two removable shelf uprights with 20 L-shaped shelf rails at vertical distances of 2.3" (57.5 mm). Convection cooling with uniform cold distribution in the interior for achieving an HACCP-compliant cold behaviour of portioned meals inserted at an interior temperature that can be controlled between +36°F and +46°F (+2 °C and +8 °C). Temperature control using digital thermostat, with gauge in top of trolley. Optimum thermal insulation through removable special sealing profiles. Four continuous vertical push bars (2 on each side), for manoeuvring even with the door open. Bumper protective feature provided by continuous bumper frame at bottom of trolley, effective also when door is open. Trolley runs on 2 swivel casters with total locks and 2 fixed casters, Ø 6.3" (160 mm), fastened by means of screw-on plates and several screws.

The Hupfer banquet trolley BKW 1 / 40 B-GN-57,5-UK has four vertical push bars to ensure effortless handling

Time and date of the request:
05.08.2025, 09:02:26

All information / dimensions are approximate, technical changes reserved. © Hupfer

Köhler® banquet trolley fan-assisted cooling 40×GN 1/1

HUPFER
we make work flow

by persons of any size even when the door is open, and the use of removable tray racks ensures optimal cleaning results, while the clearance between the sides of the racks and the side panels of the trolley ensures improved air circulation. In addition, this model provides the greatest capacity for plates with a 310 mm diameter, or GN containers in sizes GN 2/1 and GN 1/1.

Time and date of the request:
05.08.2025, 09:02:26

All information / dimensions are approximate, technical changes reserved. © Hupfer