## HUPFER we make work flow

## Service trolley with 2 compartments

P/N: 0163492 | SVW 2



Similar to illustration, technical modifications reserved. Without decoration.

## **Technical data**

**Capacity:** 4 Körbe 500x500mm, 4 Kaffeekannen

1111 mm

Modular dimension:190 mmPayload:150 kgWeight:30.699 kgWidth:862 mmDepth:655 mm

Serving trolley as mobile worktop and for provision of crockery baskets, waste containers, coffeepots and more during meal distribution using utensils inserted into tray transport trolley.

Height:

Trolley made entirely of high-quality stainless steel, self-supporting design. Open trolley made of square tubes, with two vertical partitionments on closed base plate. Left partitionment with shelf rails for storing  $19.7 \times 19.7$ " ( $500 \times 500$  mm) crockery baskets and with vertical push-through protections at the rear. Right partitionment as open compartment with intermediate shelf, suitable for storing a waste container in the lower and 4 coffeepots in the upper section, each safeguarded by horizontal galleries. Upper closing shelf with continuous profile edge and horizontal push-through protection at rear, as worktop for preparing breakfast, lunch or dinner. Capacity expansion by means of an optional frame top with capacities for up to 6 tea sets and attachment facility for plastic containers for provisioning of sugar, artificial sweetener, cream, etc. Push bars on both sides, integrated into the tube frame, ensure good manoeuvrability. 4 massive corner bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 with total locks,  $\emptyset$  4.9" (125 mm), galvanised steel housing, plastic caster wheel with roller bearing, identical to pneumatic casters and failsafe, with pin fastening.

The Hupfer service trolley SVW 2 is a welded model delivered ready for use, and provides a mobile means of preparation and provision of many utensils required for food distribution practices. The optional tow coupling provides the option of hitching the service trolley to a Hupfer tray transport trolley to form a unit that can be moved by one person. The air-free and puncture-proof running surface of the tyres ensure running noises are kept to a minimum, and make it especially suitable for uneven flooring.

Time and date of the request: 10.05.2024, 23:19:46

All information / dimensions are approximate, technical changes reserved. © Hupfer