

Tray transport cart 30 trays EN

P/N: 0164654 | TTW/V 3/30 EN 115-L PK

HUPFER
we make work flow



Technical data

Modular dimension:	115 mm
Insertion type:	Lengthwise insertion
Payload:	100
Weight:	173 kg
Width:	1537 mm
Depth:	777 mm
Height:	1646 mm

Similar to illustration, technical modifications reserved. Without decoration.

Insulated cart for transporting food on trays

Fully enclosed, double-wall insulated stainless steel transport cart. The design and materials are chosen to ensure many years of hard daily use. Smooth surfaces on the outside and inside of the cart allow hygienic cleaning. All-round polymer bumper strips on the chassis and roof effectively protect the cart from damage. DIN-quality wheels and four push bars enable easy handling of the cart. Well-sealed doors and completely insulated housing ensure that the cold chain is maintained and HACCP temperature requirements are met. With a wide range of equipment options, the cart can be adapted to individual requirements. For maximum hygienic requirements, the transport trolley interior is fully seal-welded and seamless. Together with high-quality, corrosion-resistant wheels, the transport cart is suitable for cleaning in washing devices.

Time and date of the request:
13.12.2025, 17:46:14

All information / dimensions are approximate, technical changes reserved. © Hupfer