

# Uprights with Euronorm rail pairs, 26 pairs of L-brackets for lengthwise insertion

**HUPFER**  
we make work flow



*Similar to illustration, technical modifications reserved. Without decoration.*

## Technical data

<b>Maximum dimension:</b>	530x370/325/375 mm
<b>Capacity:</b>	24 × trays EN, GN or Veska standard
<b>Modular dimension:</b>	115 mm
<b>Insertion type:</b>	Lengthwise
<b>Payload:</b>	120 kg/265 lbs
<b>Castors:</b>	2 fixed castors, 2 swivel castors with lock □ 160
<b>Main construction:</b>	Closed, single-walled, three-part
<b>Design:</b>	3 compartments, 3 × 8 runners
<b>Weight:</b>	17.919 kg
<b>Width:</b>	550 mm
<b>Depth:</b>	863 mm
<b>Height:</b>	1139 mm

Tray transport cart for storing meal components on Euronorm, Gastronorm or H+ trays.

Cart made entirely of high-quality stainless steel, self-supporting design. Single-walled tray transport cart closed on all sides. Double-walled double-wing doors that can be opened by 270° using a continuous vertical handle bar, automatic closing mechanism, single-handed operation, lock via transport latch with sealing option. Rear wall with triple rolled bead for sound insulation. Interior split in three through removable support ledge frames with 1.6/1.6" (40/40 mm) L-shaped angles, adjustable for 8 EN, GN or H+ standard trays each per compartment for lengthwise insertion. Four continuous vertical push bars (2 on each side), for easy manoeuvring. Dimensionally stable chassis design, suitable for delivery transport. In addition, the use in automatic cart transport is possible. Bumper protective feature provided by two robust, continuous bumper strips at the chassis. Cart runs on 2 swivel casters with total lock, 2 fixed casters, fastened by means of screw-on plates and four screws.

The Hupfer tray transport cart TTW / E 3/24 EN/GN 115-L features removable tray racks, providing great variability in combination with optimal cleaning results. The use of L-shaped shelf rails allows both conventional trays in the Euro norm, gastronorm and Veska norm formats as well as system trays to be used. The very low space requirements in comparison to other products, along with four vertical push bars, ensure effortless

Time and date of the request:  
03.05.2024, 15:37:46

*All information / dimensions are approximate, technical changes reserved. © Hupfer*

## Uprights with Euronorm rail pairs, 26 pairs of L-brackets for lengthwise insertion

**HUPFER**  
we make work flow

handling for persons of any size.

Time and date of the request:  
03.05.2024, 15:37:46

*All information / dimensions are approximate, technical changes reserved. © Hupfer*