

Swivel castor with lock □125 mm

P/N: 0191445151 | LR Poly/St P1/125 mF

HUPFER
we make work flow

Technical data



Payload:	100 kg
Weight:	0.6 kg
Width:	177 mm
Depth:	59 mm
Height:	165 mm

Similar to illustration, technical modifications reserved. Without decoration.

The swivel castor with a brake is used for mounting on movable devices. The swivel castor with a brake allows for the mobility, steerability, and control of the devices.

The easy-running swivel castor with brake made of high-quality plastic and metal parts made of galvanised steel is corrosion-protected and is used for mounting on wheeled equipment. The Hupfer swivel castor ensures the mobility of wheeled devices. The effortless turning, steering, and positioning of the equipment using the swivel castors increase the efficiency and safety of carrying out tasks in tight or crowded work areas. The robust swivel castor is equipped with a swivel bearing with a double ball race and allows for effortless handling of the equipment, even with heavy loads. The plain bearing enables almost silent and smooth mobility. The brakes ensure the securing and stabilisation of the device's position. The swivel castor is securely mounted to the device using a mounting plate, providing stability.

- Durable plastic housing ensures longevity - Swivel bearing with double ball ring enables effortless movement and precise control - Sliding bearing provides near-silent and smooth operation - Locking devices guarantee the securing and stabilisation of the device's position

Time and date of the request: 25.06.2025, 10:21:50 *All information / dimensions are approximate, technical changes reserved. © Hupfer*