

Norm 12/20 upright 1200×400 mm

P/N: 0201017 | RG-RS/N20/12 600kg 1200/400

HUPFER
we make work flow



Technical data

Modular dimension:	150 mm
Max. section load	600
Carbon footprint (TM65 Basic Report)	45 kgCO ₂ e
Weight:	2 kg
Width:	25 mm
Depth:	1200 mm
Height:	404 mm

Similar to illustration, technical modifications reserved. Without decoration.

Modular shelving system made of plain anodised aluminium in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of special 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 1.6 × 0.28" (40 × 7 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded shelf lugs at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request:
06.09.2025, 09:52:05

All information / dimensions are approximate, technical changes reserved. © Hupfer