


TAWALU tray clearing trolley for 10×GN

P/N: 022287-N | RTW/Z 12-5/1652

HUPFER
we make work flow



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

| | |
|---------------------------|--------------------------------------|
| Maximum dimension: | 1,200 x 500 mm shelf dimensions |
| Modular dimension: | 150 mm |
| Insertion type: | Lengthwise insertion |
| Payload: | 200 kg / 441 lbs |
| Castors: | 4 swivel castors, 2 with lock, Ø 125 |
| Main construction: | Open, flat-pack |
| Design: | Flat-pack |
| Weight: | 17 kg |
| Width: | 460 mm |
| Depth: | 687 mm |
| Height: | 1635 mm |

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 x 1.0" (25 x 25 mm) square tubes, connected and stabilised by press-fitted 2.0 x 0.12" (50 x 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded Ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 x 0.8 x 0.06" (50 x 20 x 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, Ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 12-5/1652 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request:
06.04.2026, 13:28:01

All information / dimensions are approximate, technical changes reserved. © Hupfer