

# TAWALU tray clearing trolley for 10×GN

P/N: 022287-N | RTW/Z 12-5/1652

**HUPFER**  
we make work flow



*Similar to illustration, technical modifications reserved. Without decoration.*

## Technical data

<b>Maximum dimension:</b>	1,200 x 500 mm shelf dimensions
<b>Modular dimension:</b>	150 mm
<b>Insertion type:</b>	Lengthwise insertion
<b>Payload:</b>	200 kg / 441 lbs
<b>Castors:</b>	4 swivel castors, 2 with lock, Ø 125
<b>Main construction:</b>	Open, flat-pack
<b>Design:</b>	Flat-pack
<b>Weight:</b>	17 kg
<b>Width:</b>	460 mm
<b>Depth:</b>	687 mm
<b>Height:</b>	1635 mm

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 x 1.0" (25 x 25 mm) square tubes, connected and stabilised by press-fitted 2.0 x 0.12" (50 x 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded Ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 x 0.8 x 0.06" (50 x 20 x 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, Ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 12-5/1652 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request:  
20.05.2026, 08:02:35

*All information / dimensions are approximate, technical changes reserved. © Hupfer*