

Norm 12 segment B550×T400

P/N: 0602999911 | RTW/Z 14-5/900

HUPFER
we make work flow



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Maximum dimension:	1,400 x 500 mm shelf dimensions
Modular dimension:	150 mm
Shelf dimensions:	1,400 x 500 mm
Payload:	200 kg / 441 lbs
Castors:	4 swivel castors, 2 with lock, Ø 125
Main construction:	Open, flat-pack
Design:	Flat-pack
Weight:	1 kg
Width:	547 mm
Depth:	384 mm
Height:	50 mm

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 x 1.0" (25 x 25 mm) square tubes, connected and stabilised by press-fitted 2.0 x 0.12" (50 x 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded Ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 x 0.8 x 0.06" (50 x 20 x 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, Ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 14-5/900 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request:
05.08.2025, 02:09:10

All information / dimensions are approximate, technical changes reserved. © Hupfer