

# Känguruh push-in rack 6 StU

P/N: 7504622 | KÄ-EG 6StE 685/615/1041 L-Sch

**HUPFER**  
we make work flow



## Technical data

**Modular dimension:** 61.5 mm

**TM65 Midlevel Report** [Link to the certificate](#)

**Weight:** 24 kg

**Width:** 685 mm

**Depth:** 615 mm

**Height:** 1041 mm

*Similar to illustration, technical modifications reserved. Without decoration.*

Rack frame for storing sterilisation units.

Rack with two compartments in robust, self-supporting, hygienic and sterilisable design, made of high-quality stainless steel square tubes with 15 pairs of shelf bolts each, at a modular dimension of 2.4" (61.5 mm) for height-adjustable L-shaped insert rails and one additional bolt each, located centrally in between the third and fourth shelf bolt from top. It enables holding an additional disposal container measuring 23.6 × 11.8 × 7.9" (600 × 300 × 200 mm). Safe connection of rack and receiving system component (transport trolley, transfer dolly or base frame) by means of a locking wire that is released by lifting at the upper side of the rack. Once the rack has been retracted until it has reached the locking point and the wire is let loose, the wire latches safely and audibly into an anchor block. Two guide rails, made of stainless steel sheet and arranged in longitudinal direction underneath the rack, provide additional safety along with matching guide rollers at the relevant system component. Mobile rack frame runs on 4 sterilisable fixed casters with ø 3.0" (75 mm) caster body made of polymer.

Time and date of the request:  
05.04.2026, 03:23:17

*All information / dimensions are approximate, technical changes reserved. © Hupfer*