

Sterile goods transport cart for 6 StU

P/N: 7504647 | RTW/Z 10-6/1652

HUPFER
we make work flow

Technical data



Payload:	200 kg
Weight:	91 kg
Width:	985 mm
Depth:	751 mm
Height:	1471 mm

Similar to illustration, technical modifications reserved. Without decoration.

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of $1.0 \times 1.0"$ (25 × 25 mm) square tubes, connected and stabilised by press-fitted $2.0 \times 0.12"$ (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded $\varnothing 0.28"$ (7 mm) shelf bolts at distances of $5.9"$ (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four $2.0 \times 0.8 \times 0.06"$ (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, $\varnothing 4.9"$ (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 10-6/1652 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request: 04.02.2026, 10:39:27 All information / dimensions are approximate, technical changes reserved. © Hupfer