

## Packing table 1200×650×850-1150 mm

P/N: 7505798 | PT-EH 1600/700/850-1150 F

**HUPFER**  
we make work flow



*Similar to illustration, technical modifications reserved. Without decoration.*

### Technical data

<b>Maximum dimension:</b>	1,600 × 700 mm
<b>Base dimensions:</b>	1,450 × 600 mm
<b>Rectangular tubing base:</b>	40 × 40 mm
<b>Height adjustment (stroke):</b>	300 mm
<b>Worktop thickness:</b>	1.5 mm
<b>Bevelled worktop edges:</b>	50 mm
<b>Payload:</b>	235 kg/518 lbs
<b>Castors:</b>	4 swivel castors, 2 with lock, Ø 125
<b>Main construction:</b>	Open
<b>Capacity:</b>	240 W
<b>Supply voltage:</b>	230 V AC
<b>Nominal current:</b>	1.04 A
<b>Protection class:</b>	IPX4
<b>Frequency:</b>	50 Hz
<b>Weight:</b>	102 kg
<b>Width:</b>	1200 mm
<b>Depth:</b>	650 mm
<b>Height:</b>	850 mm

Packing table made of high-quality stainless steel in hygienic design, with hydraulic height adjustment system for ergonomic adaptation to different body sizes.

Robust design made of square tubes, worktop folded on all sides. Underside of tabletop reinforced by profiles and fitted with a stainless steel pan, housing and protecting the hydraulic system for height adjustment. Lift cylinders with adjustment feet ensure compensation of floor unevennesses. Hydraulic, infinitely variable height adjustment system integrated into feet, for adaptation to different user body heights. Chassis with four feet for worktops up to a length of 87" (2200 mm), with six feet for greater lengths, mobile on swivel casters with back-hole fastening, two of which with total lock. Struts in base on three sides for enhanced rigidity and optimum attaching of shelves.

Time and date of the request: 25.01.2026, 13:47:38 All information / dimensions are approximate, technical changes reserved. © Hupfer

## Packing table 1200×650×850-1150 mm

P/N: 7505798 | PT-EH 1600/700/850-1150 F

The Hupfer height-adjustable and mobile packing table PT-EH 1600/700/850-1150-F allows infinite height adjustment, ensuring it provides a wide range of individual options for use, as well as options for adapting it to diverse circumstances. The digital display ensures an exact and easy-to-read indication of the set working height.