

Refrigerated well with cooling unit GN 4/1

P/N: 8900424 | A-GS/N12 0900/500



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Max. bay load	200
Carbon footprint (TM65 Basic Report)	39 kgCO ₂ e
Payload:	60
Capacity:	1000 W
Cooling capacity:	1600 W
Supply voltage:	230 V
Nominal current:	4,2 A
Protection class:	Class I
Frequency:	50 Hz
Weight:	149 kg
Width:	1374 mm
Depth:	690 mm
Height:	710 mm

Closed support made of polystyrene segments on aluminium support beams.

The effortlessly attachable, enclosed plastic tray offers a lightweight, secure, and very easy-to-clean surface, even in the dishwasher. This tray for the Norm 12 shelf can support high loads despite its low weight. Temperatures of -30°C are not a problem even in the long term. The materials used are sustainable, 100% recyclable, and so valuable that Hupfer already guarantees to buy back your entire shelf at the end of its service life.

- Closed design in plastic with low weight ensures safe, hygienic storage and clear access at all times
- Quality processing of high-quality plastic enables perfect hygiene and easy cleaning even in the dishwasher
- Valuable materials ensure sustainability and value retention
- Stable construction guarantees high load capacity
- Modular system ensures easy handling from assembly to cleaning with

Time and date of the request: 22.02.2026, 10:14:14 All information / dimensions are approximate, technical changes reserved. © Hupfer

Refrigerated well with cooling unit GN 4/1

P/N: 8900424 | A-GS/N12 0900/500

minimal effort

Time and date of the request: 22.02.2026, 10:14:14 *All information / dimensions are approximate, technical changes reserved. © Hupfer*