

# Refrigerated well with cooling unit GN 5/1

P/N: 8900425 | A-BR/N5 1000/400

**HUPFER**  
we make work flow

## Technical data



*Similar to illustration, technical modifications reserved. Without decoration.*

<b>Max. bay load</b>	150
<b>Carbon footprint (TM65 Basic Report)</b>	28 kgCO <sub>2</sub> e
<b>Payload:</b>	75 kg
<b>Capacity:</b>	1250 W
<b>Cooling capacity:</b>	2200 W
<b>Supply voltage:</b>	230 V
<b>Nominal current:</b>	5,4 A
<b>Protection class:</b>	Class I
<b>Frequency:</b>	50 Hz
<b>Weight:</b>	170 kg
<b>Width:</b>	1699 mm
<b>Depth:</b>	690 mm
<b>Height:</b>	710 mm

Stainless steel slatted sheet steel support made of 0.03" (0.8 mm) thick sheet steel, with burr-free cutting edges, folded and rebated inwards 1.6" (40 mm) at the long side and 1.2" (30 mm) at the face side. Deep-pressed, approx. 1.3" (32 mm) wide slots at distances of 2.0" (50 mm).

Time and date of the request:  
19.07.2025, 07:45:30

*All information / dimensions are approximate, technical changes reserved. © Hupfer*