

2000 mm

## **Stationary shelving set norm 12 with solid shelf**

P/N: N12GS29006002000 | RG-RS/N20/12 600kg 1400/300

## Technical data



Similar to illustration, technical modifications reserved. Without decoration.

Modular dimension:150 mmMax. section load600Carbon footprint (TM65 Basic Report)50 kgCOIleWeight:55 kgWidth:2850 mmDepth:600 mm

Modular shelving system made of plain anodised aluminium in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140 $^{\circ}$ F (-40 to +60 $^{\circ}$ C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Height:

Uprights made of special  $1.0 \times 1.0$ " (25 × 25 mm) square tubes, connected and stabilised by press-fitted  $1.6 \times 0$ . 28" (40 × 7 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded shelf lugs at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request: 13.09.2025, 17:21:33

All information / dimensions are approximate, technical changes reserved. © Hupfer