

# Stationary shelving set norm 12 with solid shelf

**HUPFER**  
we make work flow

P/N: N12GS40005002000 | RTW/Z EB 5-6/1850

## Technical data



<b>Modular dimension:</b>	150 mm
<b>Carbon footprint (TM65 Basic Report)</b>	1435 kgCO <sub>2</sub> e
<b>Payload:</b>	80 kg
<b>Weight:</b>	67 kg
<b>Width:</b>	3950 mm
<b>Depth:</b>	500 mm
<b>Height:</b>	2000 mm

*Similar to illustration, technical modifications reserved. Without decoration.*

Mobile shelving unit made of high-quality stainless steel in hygienic design according to DIN 18868-2 for transport and intermediate storage of delivered goods in Euro containers.

Uprights made of rectangular tubes 25 × 25 mm, connected and stabilised by hard pressed transverse upright rungs, 50 × 3 mm. Upper covering cap made of plastic as hygienic closure of the upright. Permanently welded shelf bolts  $\varnothing$  7 mm at a distance of 75 mm for easy hooking on the shelf rests. Stiffening with 4 screwable bracing bars 50 × 20 × 1.5 mm 4 polyethylene disc bumpers serve as bumpers and protect both the trolley on all sides as well as on-site walls against damage. Mobile shelving unit with 4 swivel castors, two of which with total brake, average 125 mm, plastic housing, plastic wheel with stainless steel ball bearings, according to DIN 188678, back-hole fastening. Special features The Hupfer mobile shelving unit for Euro containers RTW/Z EB 5-6/1850 provides the ideal shelf dimensions and adjustment possibilities for transport and access-friendly intermediate storage of goods delivered in euro-containers.

The Hupfer mobile shelving unit for Euro containers RTW/Z EB 5-6/1850 provides ideal shelf dimensions and adjustment options for transport and easily accessible interim storage of goods delivered in Euro containers.

Time and date of the request:  
15.09.2025, 10:14:46

*All information / dimensions are approximate, technical changes reserved. © Hupfer*