

2000 mm

## Stationary shelving set norm 12 with solid shelf

P/N: N12GS40005002000 | RTW/Z EB 5-6/1850

## **Technical data**



Similar to illustration, technical modifications reserved. Without decoration.

Modular dimension:150 mmCarbon footprint (TM65 Basic Report)807 kgCOllePayload:80 kgWeight:67 kgWidth:3950 mmDepth:500 mm

Mobile shelving unit made of high-quality stainless steel in hygienic design according to DIN 18868-2 for transport and intermediate storage of delivered goods in Euro containers.

Height:

Uprights made of rectangular tubes  $25 \times 25$  mm, connected and stabilised by hard pressed transverse upright rungs,  $50 \times 3$  mm. Upper covering cap made of plastic as hygienic closure of the upright. Permanently welded shelf bolts ø 7 mm at a distance of 75 mm for easy hooking on the shelf rests. Stiffening with 4 screwable bracing bars  $50 \times 20 \times 1.5$  mm 4 polyethylene disc bumpers serve as bumpers and protect both the trolley on all sides as well as on-site walls against damage. Mobile shelving unit with 4 swivel castors, two of which with total brake, average 125 mm, plastic housing, plastic wheel with stainless steel ball bearings, according to DIN 188678, back-hole fastening. Special features The Hupfer mobile shelving unit for Euro containers RTW/Z EB 5-6/1850 provides the ideal shelf dimensions and adjustment possibilities for transport and access-friendly intermediate storage of goods delivered in euro-containers.

The Hupfer mobile shelving unit for Euro containers RTW/Z EB 5-6/1850 provides ideal shelf dimensions and adjustment options for transport and easily accessible interim storage of goods delivered in Euro containers.

Time and date of the request: 13.12.2025, 21:24:28

All information / dimensions are approximate, technical changes reserved. © Hupfer