Stationary shelving set norm 12 with solid shelf

we make work flow

P/N: N12GS48004002000 | TTW/V 2/24 EN 115-L

Technical data



Similar to illustration, technical modifications reserved. Without decoration.

Cleaning classification:	Suitable for washing devices
Maximum dimension:	530 × 370 mm
Capacity:	24 EN trays
Modular dimension:	115 mm
Insertion type:	Lengthwise
Max. bay load	150
Max. section load	600
Carbon footprint (TM65 Basic Report)	1590 kgCO⊡e
Payload:	120 kg/265 lbs
Payload: Castors:	120 kg/265 lbs 2 fixed castors, 2 swivel castors with lock 🛛 160
-	2 fixed castors, 2 swivel castors
Castors:	2 fixed castors, 2 swivel castors with lock 🛛 160
Castors: Main construction:	2 fixed castors, 2 swivel castors with lock 🛛 160 Closed, double-walled, two-part
Castors: Main construction: Design:	2 fixed castors, 2 swivel castors with lock 🛛 160 Closed, double-walled, two-part Welded on inside
Castors: Main construction: Design: Weight:	2 fixed castors, 2 swivel castors with lock 🛛 160 Closed, double-walled, two-part Welded on inside 69 kg

Tray transport cart for storing meal components on Euronorm trays.

Cart made entirely of high-quality stainless steel, self-supporting design. Double-walled tray transport cart closed on all sides, with welded interior suitable for washing devices. Wall and doors thermally insulated CFCfree. Double-walled double-wing doors, can be opened by 270°, automatic closing mechanism, operation with one hand. Additional locking at 255° to prevent areas from being left unrinsed in the cart washing device. Door lock through integrated 2-point locking. Welded interior with two partitionments for 12 EN trays each, for lengthwise insertion. Side panels with seamless deep-drawn shelf beads as tray shelves at height intervals of 4.53" (115 mm), with additional stamped tilt protections. Four continuous vertical push bars (2 on each side) for manoeuvring even with the doors open. Dimensionally stable chassis design, suitable for delivery transport. In addition, the use in automatic cart transport is possible. Bumper protective feature provided by two robust

All information / dimensions are approximate, technical changes reserved. © Hupfer Time and date of the request: 18.07.2025, 05:35:47

Hupfer · Dieselstrasse 20, 48653 COESFELD · Postfach 1463, 48634 COESFELD · Tel.: +49 2541 805-0 · Fax: +49 2541 805-111 info@hupfer.de · www.hupfer.com

Stationary shelving set norm 12 with solid shelf



P/N: N12GS48004002000 | TTW/V 2/24 EN 115-L

continuous bumper strips at the chassis, effective also when doors are open. Cart runs on 2 swivel casters with total lock, 2 fixed casters, fastened by means of screw-on plates and four screws.

- solid polymer shelf with low weight ensures safe, hygienic storage and clear access at all times
- high-quality polymer workmanship allows for easy cleaning and perfect hygiene. It is even dishwasher safe.
- modular system allows for any design and extension and ensures the most efficient use of space
- valuable materials ensure sustainability and value retention
- robust construction guarantees high stability and high load-bearing capacity
- modular system ensures easy handling from assembly to cleaning with little effort