

Stationary shelving set norm 12 with solid shelf

HUPFER
we make work flow

P/N: N12GS9006002000 | RG-RS/N20/12 1200kg 2000/400

Technical data



Modular dimension:	150 mm
Max. section load	1200
Carbon footprint (TM65 Basic Report)	277 kgCO ₂ e
Weight:	20 kg
Width:	900 mm
Depth:	600 mm
Height:	2000 mm

Similar to illustration, technical modifications reserved. Without decoration.

Modular shelving system made of plain anodised aluminium in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of special 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 1.6 × 0.28" (40 × 7 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded shelf lugs at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request:
10.04.2026, 08:59:10

All information / dimensions are approximate, technical changes reserved. © Hupfer