

Stationary shelving set norm 12 with louvred shelf

HUPFER
we make work flow

Technical data



Modular dimension:	150 mm
Carbon footprint (TM65 Basic Report)	615 kgCO ₂ e
Payload:	120 kg
Weight:	40 kg
Width:	2575 mm
Depth:	500 mm
Height:	2000 mm

Similar to illustration, technical modifications reserved. Without decoration.

Serving trolley in heavy ERGO version with deep-drawn shelves.

Trolley in robust, self-supporting and hygienic design, made of high-quality stainless steel. Closed, continuous round tube frame with welded, deep-drawn shelves with profile edge, lined with sound insulation on the underside, hygienically folded and rebated inwards, designed for easy cleaning. As standard, the shelves are equipped with reinforcement struts on the underside, consisting of one diagonal and two longitudinal struts that are fully welded to each other. Push bars integrated on both sides into tube frame ensure good manoeuvrability. Optimised handling through ergonomic shape of one push bar up to a height of 49.2" (1250 mm). 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Trolley runs on 4 swivel casters of which 2 are equipped with total locks, and on one central fixed caster, \varnothing 7.9" (200 mm), fastened to additional reinforcement crossbars by means of screw-on plates and several screws.

The Hupfer serving trolley SSW 8 x 5 / 2 ERGO is a welded model delivered ready for use, and features an ergonomically optimised push bar with an installation height that gives the user horizontal and vertical access, and ensures comparatively fatigue-free use. In addition, the large castors guarantee extremely low rolling resistance. The smooth and cavity-free raised edges makes this model easy to clean, and prevents dirt from accumulating in the corners.

Time and date of the request: 20.04.2026, 23:47:32 *All information / dimensions are approximate, technical changes reserved. © Hupfer*