

# Stationary shelving set norm 12 with louvred shelf

**HUPFER**  
we make work flow

## Technical data



*Similar to illustration, technical modifications reserved. Without decoration.*

<b>Modular dimension:</b>	150 mm
<b>Carbon footprint (TM65 Basic Report)</b>	367 kgCO <sub>2</sub> e
<b>Payload:</b>	200 kg
<b>Weight:</b>	11 kg
<b>Width:</b>	600 mm
<b>Depth:</b>	400 mm
<b>Height:</b>	1800 mm

Mobile shelving unit made of high-quality stainless steel in hygienic design according to DIN 18868-2 for transport and intermediate storage of delivered goods in Euro containers.

Uprights made of rectangular tubes 25 × 25 mm, connected and stabilised by hard pressed transverse upright rungs, 50 × 3 mm. Upper covering cap made of plastic as hygienic closure of the upright. Permanently welded shelf bolts  $\varnothing$  7 mm at a distance of 75 mm for easy hooking on the shelf rests. Stiffening with 4 screwable bracing bars 50 × 20 × 1.5 mm 4 polyethylene disc bumpers serve as bumpers and protect both the trolley on all sides as well as on-site walls against damage. Mobile shelving unit with 4 swivel castors, two of which with total brake, average 125 mm, plastic housing, plastic wheel with stainless steel ball bearings, according to DIN 18867-8 with back-hole fastening. Special features The Hupfer mobile shelving unit for Euro containers RTW/Z EB 106/1850 provides the ideal shelf dimensions and adjustment possibilities for transport and access-friendly intermediate storage of goods delivered in euro-containers.

The Hupfer mobile shelving unit for Euro containers RTW/Z EB 10-6/1850 provides ideal shelf dimensions and adjustment options for transport and easily accessible interim storage of goods delivered in Euro containers.

Time and date of the request:  
15.08.2025, 08:39:49

*All information / dimensions are approximate, technical changes reserved. © Hupfer*