

2000 mm

Stationary shelving set norm 20 with slatted shelf

Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Modular dimension:150 mmCarbon footprint (TM65 Basic Report)566 kgCOllePayload:200 kgWeight:26 kgWidth:1875 mmDepth:500 mm

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Height:

Uprights made of 1.0×1.0 " (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0×0.12 " (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded ø 0. 28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four $2.0 \times 0.8 \times 0.06$ " (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 12-5/1652 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request: 02.11.2025, 13:50:15

All information / dimensions are approximate, technical changes reserved. © Hupfer