

Stationary shelving set norm 20 with slatted shelf

Similar to illustration, technical modifications reserved. Without decoration.

Technical data

1,400 x 500 mm shelf **Maximum dimension:**

dimensions

Modular dimension: 150 mm

Max. bay load 150

Max. section load

Carbon footprint (TM65 Midlevel 209 kgCO□e

TM65 Midlevel Report Link to the certificate

Payload: 200 kg / 441 lbs

4 swivel castors, 2 with lock, Ø **Castors:**

125

600

Main construction: Open, flat-pack

Design: Flat-pack Weight: 10 kg Width: 800 mm 300 mm Depth: Height: 1600 mm

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0×1.0 " (25 x 25 mm) square tubes, connected and stabilised by press-fitted 2.0×0.12 " (50 x 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded Ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 x 0.8 x 0.06" (50 x 20 x 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, Ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 14-5/1652 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request: 06.12.2025, 22:08:44

All information / dimensions are approximate, technical changes reserved. © Hupfer