

# Stationary shelving set norm 20 with slatted shelf

**HUPFER**  
we make work flow

## Technical data



*Similar to illustration, technical modifications reserved. Without decoration.*

|  |   |
|--|---|
| <b>Maximum dimension:</b>                      | 1,400 x 500 mm shelf dimensions         |
| <b>Modular dimension:</b>                      | 150 mm                                  |
| <b>Max. bay load</b>                           | 150                                     |
| <b>Max. section load</b>                       | 600                                     |
| <b>Carbon footprint (TM65 Midlevel Report)</b> | 209 kgCO <sub>2</sub> e                 |
| <b>TM65 Midlevel Report</b>                    | <a href="#">Link to the certificate</a> |
| <b>Payload:</b>                                | 200 kg / 441 lbs                        |
| <b>Castors:</b>                                | 4 swivel castors, 2 with lock, Ø 125    |
| <b>Main construction:</b>                      | Open, flat-pack                         |
| <b>Design:</b>                                 | Flat-pack                               |
| <b>Weight:</b>                                 | 10 kg                                   |
| <b>Width:</b>                                  | 800 mm                                  |
| <b>Depth:</b>                                  | 300 mm                                  |
| <b>Height:</b>                                 | 1600 mm                                 |

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 x 1.0" (25 x 25 mm) square tubes, connected and stabilised by press-fitted 2.0 x 0.12" (50 x 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded Ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 x 0.8 x 0.06" (50 x 20 x 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, Ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 14-5/1652 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request: 29.12.2025, 23:02:39 *All information / dimensions are approximate, technical changes reserved. © Hupfer*