

# Stationary shelving set norm 20 with slatted shelf

**HUPFER**  
we make work flow

## Technical data



|   |                         |
|---|-------------------------|
| <b>Modular dimension:</b>                   | 150 mm                  |
| <b>Carbon footprint (TM65 Basic Report)</b> | 310 kgCO <sub>2</sub> e |
| <b>Payload:</b>                             | 200 kg                  |
| <b>Weight:</b>                              | 15 kg                   |
| <b>Width:</b>                               | 900 mm                  |
| <b>Depth:</b>                               | 600 mm                  |
| <b>Height:</b>                              | 1400 mm                 |

*Similar to illustration, technical modifications reserved. Without decoration.*

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.12" (50 × 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded ø 0. 28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 × 0.8 × 0.06" (50 × 20 × 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 10-6/900 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request:  
26.02.2026, 09:45:30

*All information / dimensions are approximate, technical changes reserved. © Hupfer*