

Stationary shelving set norm 20 with solid shelf

HUPFER
we make work flow

P/N: N20GS30003001400 | RG-RS/N20/12 600kg 2000/500

Technical data



Modular dimension:	150 mm
Max. section load	600
Carbon footprint (TM65 Basic Report)	75 kgCO ₂ e
Weight:	27 kg
Width:	2950 mm
Depth:	300 mm
Height:	1400 mm

Similar to illustration, technical modifications reserved. Without decoration.

Modular shelving system made of plain anodised aluminium in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of special 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 1.6 × 0.28" (40 × 7 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded shelf lugs at distances of 5.9" (150 mm) for easy attaching of shelves.

Time and date of the request:
10.04.2026, 20:21:42

All information / dimensions are approximate, technical changes reserved. © Hupfer