

## Stationary shelving set norm 20 with solid shelf

P/N: N20GS42004001800 | RTW/Z 12-5/1200



Similar to illustration, technical modifications reserved. Without decoration.

## **Technical data**

Max. section load

1,200 x 500 mm shelf **Maximum dimension:** dimensions

Modular dimension: 150 mm

Max. bay load 150

**Carbon footprint (TM65 Midlevel** 1057 kgCO□e

Report)

**TM65 Midlevel Report** Link to the certificate

Payload: 200 kg / 441 lbs

4 swivel castors, 2 with lock, Ø **Castors:** 

125

600

Main construction: Open, flat-pack

Design: Flat-pack Weight: 49 kg Width: 4125 mm 400 mm Depth: Height: 1800 mm

Displaceable shelf made of high-quality stainless steel in hygienic design as per DIN 18868-2.

Uprights made of  $1.0 \times 1.0$ " (25 x 25 mm) square tubes, connected and stabilised by press-fitted  $2.0 \times 0.12$ " (50 x 3 mm) upright spokes running crosswise. Upper covering caps made of plastic, as hygienic ending of upright. Welded Ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves. Shelves in hygienic design for easy cleaning. Stiffening through four 2.0 x 0.8 x 0.06" (50 x 20 x 1.5 mm) long rails. 4 polyethylene disc bumpers serve as bumpers and protect trolley on all sides as well as building-side walls from being damaged. Mobile shelving unit with 4 swivel casters of which two with total lock, Ø 4.9" (125 mm), with back-hole fastening.

The Hupfer mobile shelving unit RTW/Z 12-5/1200 features extensive equipment options, allowing a wide range of individual options for use as well as adjustment options for diverse space requirements and temperature conditions.

Time and date of the request: 07.12.2025, 07:12:16

All information / dimensions are approximate, technical changes reserved. © Hupfer