

Stationary shelving set norm 20 with solid shelf

P/N: N20GS7006001400 | RG-RS/N5 1200kg 2000/300

Technical data

Similar to illustration, technical modifications reserved. Without decoration.

Modular dimension:	150 mm
Max. bay load	150
Max. section load	600
Carbon footprint (TM65 Midlevel Report)	275 kgCO ₂ e
TM65 Midlevel Report	Link to the certificate
Weight:	13 kg
Width:	700 mm
Depth:	600 mm
Height:	1400 mm

Modular shelving system made of high-quality stainless steel 1.4301 in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140°F (-40 to +60 °C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of 1.0 × 1.0" (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0 × 0.08" (50 × 2 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded ø 0.28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves.

- solid shelf made from lightweight aluminium ensures easy handling, safe, hygienic storage and clear access at all times
- high-quality aluminium workmanship enables easy cleaning and perfect hygiene
- modular system allows for any design and extension and ensures the most efficient use of space
- valuable materials ensure sustainability and value retention
- robust construction guarantees high stability and high load-bearing capacity
- modular system ensures easy handling from assembly to cleaning with little effort

Time and date of the request:
23.02.2026, 08:57:35

All information / dimensions are approximate, technical changes reserved. © Hupfer