


Stationary shelving set norm 35 with wire shelf

HUPFER
we make work flow

P/N: N35DR44005102000 | CTW/VV 6StE 965/754/1445

Technical data



Modular dimension:	300 mm
Carbon footprint (TM65 Basic Report)	1042 kgCO ₂ e
Payload:	150 kg
Weight:	108 kg
Width:	4325 mm
Depth:	510 mm
Height:	2000 mm

Similar to illustration, technical modifications reserved. Without decoration.

Transport trolley for transport and storage of sterile supplies in containers or baskets.

Single-walled trolley structure closed on all sides in fully welded design, suitable for washing devices. Double-walled double-wing doors with continuous seals, can be opened by 270°, automatic closing mechanism, operation with one hand. Door lock through integrated 2-point locking. Interior equipped as standard with removable L-shaped shelf rails that are height-adjustable within the entire interior height. Rails for holding sterile supplies baskets or containers. Four continuous vertical push bars (2 per side) for manoeuvring even with the doors open. Bumper protective feature provided by robust, continuous bumper strip that is effective also with the doors open, with frontal recesses for connecting a towing device to the chassis. Trolley runs on 2 swivel casters with total lock, 2 fixed casters, fastened by means of screw-on plates and several screws.

Time and date of the request:
22.05.2026, 06:46:33

All information / dimensions are approximate, technical changes reserved. © Hupfer