

150 mm

Stationary shelving set norm 5 with louvred shelfwe make work flow

P/N: N5BR18005002000 | RG-RS/N25 600kg 2000/500



Similar to illustration, technical modifications reserved. Without decoration.

Technical data

Modular dimension:

Max. bay load 150

Max. section load 600

Carbon footprint (TM65 Midlevel Report) 374 kgCOlle

TM65 Midlevel Report Link to the certificate

 Weight:
 41 kg

 Width:
 1775 mm

 Depth:
 500 mm

 Height:
 2000 mm

Modular shelving system made of high-quality stainless steel in hygienic design as per DIN 18868-2, suitable for continuous use at -40 to +140 $^{\circ}$ F (-40 to +60 $^{\circ}$ C), for arrangement in a straight line or for angled setup with corner hooks, freely extendable lengthwise.

Uprights made of 1.0×1.0 " (25 × 25 mm) square tubes, connected and stabilised by press-fitted 2.0×0.08 " (50 × 2 mm) upright spokes running crosswise. Upper covering caps made of plastic, height-adjustable screw feet for compensating floor unevennesses of up to 1.0" (25 mm) as hygienic ending of upright. Welded Ø 0. 28" (7 mm) shelf bolts at distances of 5.9" (150 mm) for easy attaching of shelves.

- louvred shelf ensures ventilated, safe and hygienic storage and keeps the stored goods in peak condition
- high-quality stainless steel workmanship enables easy cleaning and perfect hygiene
- modular system allows for any design and extension and ensures the most efficient use of space
- valuable materials ensure sustainability and value retention
- robust construction guarantees high stability and high load-bearing capacity
- modular system ensures easy handling from assembly to cleaning with little effort

Time and date of the request: 18.11.2025, 14:03:40

All information / dimensions are approximate, technical changes reserved. © Hupfer